



FILLING SYSTEM ELEMENTRA®

Meet the intuitive generation







ELEMENTRA® 29

ELEMENTRA® 29 for high-viscosity products

The servo technology of the **ELEMENTRA® 29** (FEIGE e-Power) makes it possible to adapt the entire lifting process during filling to the respective product via control-related parameters.

Thanks to extensive peripherals, the semi-automatic system meets the special requirements of the filling products and the respective

The new touch panel including the FEIGE web HMI offers an intuitive design for high operating comfort.

- Electric lifting unit
- Automatic positioning when changing container
 Saving expensive energy (compressed air)
 Exhaust-free use also in clean rooms
 With-surface filling possible

- 2 Electric base height adjustment
- Automatic positioning when changing container
 Saving expensive energy (compressed air)
 Exhaust-free use also in clean rooms
 Ergonomic handling for the operator

- 3 Electrically driven drum roller conveyor
- Automatic drum positioning via light barrier
 All rollers with chains and gear motors driven
 Ergonomic further transport of filled drums
- 4 WEB HMI
- Alarm-related help texts with photos, videos and comment function Intuitive design for high operating comfort
 Improved usability increases the productivity of the personnel 15,6" multi touch screen
 Full HD display
 Comprehensive management of recipes and orders
 FDA-compliant user administration
 Logbook (optional)
 Web-based system

5 Fill level and status indication Interactive operation by means of LED stripes included in the control cabinet door, informing the operator of every machine status
 Weight-controlled fill level indication 6 Large control cabinet High flexibility due to standardized machine control
 Control up to five drive units 7 Stainless steel / acid protection coating Design elements at the control cabinet made of stainless steel with high-quality acid protection coating 8 With-surface filling The valve tip has a "thread-cutting" effect, therefore suitable for high-viscosity or sticky filling products
Continuous upward movement of the filling valve without breaking the product flow
Upward movement with the product level without immersing or preceding

* Fig. includes special equipment

3

HAVER & BOECKER - INTERPACK 2023 STAND HALLE 12/A27

HAVER & BOECKER

PACKING



Phone: +49 (0) 2522 30-0

E-mail: haver@haverboecker.com

QUAT²RO

DIGITALIZATION

Phone: +49 (0) 251 208 163 50 E-mail: info@quat2ro.com

BEHN+BATES

PACKING



Phone: +49 (0) 251 9796-0 E-mail: sales@behnbates.com



PACKING

Phone: +49 (0) 2581 4591-1139 E-mail: info@aventus.global

NEWTEC BAG PALLETIZING

PALLETIZING+LOADING



Phone: +33 389 633750 E-mail: info@newtecbag.com

Feige FILLING GmbH

Rögen 6a

D-23843 Bad Oldesloe

Germany

Phone: +49 4531 8909 0 E-mail: info@feige.com Internet: www.feige.com

